



ALSEAL

Stick to Alseal's Quality



Perimeter Sealing

Gap Between Wall & Cabinet

Wood Skirting



AS-1120 Ultra Flex Gaps Sealer

ALSEAL Ultra Flex Gap Sealer is a premium grade high elastic acrylic sealant for both external and internal sealing applications. It is formulated with enhanced UV resistance property and can withstand up to 25% movement. It is paintable and formulated for sealing gaps and joints where high movements or vibrations are expected.

Applications:

It is ideal for external & internal sealing applications. It is good for sealing of building joints that are subject to movement (door and window joints, cabinet and wardrobe installation, skirting of wood flooring, etc.). Suitable for various substrates (metal, PVC, wood, concrete, gypsum boards, reinforced cement boards, marble, etc.).

Approvals / Specifications:

- ▶ ASTM C920, Type S, Grade NS, Class 25, Use NT, M
- ▶ Low VOC - USEPA Method 24 and SCAQMD Method 304-91 under SCAQMD Rule 1168

Available colour: White

Features:

- ✓ ±25% Movement capability
- ✓ Exterior & Interior sealant applications
- ✓ Paintable
- ✓ Permanently flexible & easy clean up

Product Code	Content	Carton Quantity
AS-1120	450 g / Cartridge	24 / Carton