



Wood Flooring



PU Stone



AS-4036 MS Floor and Wall Bonds

ALSEAL MS Floor and Wall Bonds is a universal construction adhesive based on advanced MS Polymer technology. It cures on exposure to atmospheric moisture, and forms an elastic bond on general building materials, including porous and non-porous surfaces, floors, wall decorative and panels. The adhesive can be troweled easily. It has good weathering and UV resistance properties. This product does not contain hazardous materials like isocyanate, solvents, halogens, and acid.

Applications: Ideal for bonding all types of building materials – including porous and non-porous substrates on horizontal and vertical surfaces: concrete, concrete screeds, cement / sand screeds, anhydrite screeds, wood, artificial grass, plywood, cured leveling compounds, epoxy membrane, OSB (underlayment grade), particle board, gypsum board, ceramic tiles, stone, terrazzo, radiant heated subfloors, metal decking, steel, aluminum, etc.

Available colour: White

Features:

- ✓ Excellent adhesion on most substrates
- ✓ Notched trowel ridges hold firm
 - Minimize hollow spots by bridging gaps
- ✓ Resistant to aging – Permanently elastomeric
- ✓ Workability – Easy to tool
- ✓ Good weathering performance – UV resistance
- ✓ Paintable
- ✓ Free of water, 100% solid content
 - No dimensional changes in wood
- ✓ Single-component – Ready for use, no mixing required
- ✓ Free of isocyanate and formaldehyde
 - Non hazardous formulation
- ✓ Easy surface clean up – Easy cleaning on substrates
- ✓ Non-flammable, stable shelf life – Easy storage

Product Code	Content	Carton Quantity
AS-4036-16K	16 kg (2 x 8 kg packs in pail)	-
AS-4036-24K	24 kg (3 x 8 kg packs in pail)	-
AS-4036S	600 ml / sausage	20 / Carton