

# Technical Data Sheet

## AS-3070 Roofing Tape



### Physical Properties

**Principal Composition:** Butyl rubber

**Appearance:**  
Grey

**Odour:**  
None or very little

**Service Temperature:**  
-15 °C to 80 °C

**Storage:**  
Store away from direct sunlight and heat source, keep under cold and shaded place.

**Shelf Life:**  
12 months

#### Packaging:

Size	Quantity/ carton
9 mm x 2.5 mm x 19.0 m	20
12.0 mm x 2.5 mm x 19.0 m	20
19.0 mm x 2.5 mm x 19.0 m	20

### Description

ALSEAL Roofing Tape is a double-sided butyl adhesive tape that has high cohesive and adhesive strengths. It contains anti-oxidants, fungicides and anti-bacterial agents and available in several sizes.

### Features

- ♦ High cohesive and adhesive strengths
- ♦ Anti-oxidants, fungicides, and anti-bacterial agents

### Applications

It is used on built-up roof to seal end laps and the side laps of the top (weather) sheet. Other applications are sealing around rooflights, gutters and flashings. It is suitable for both clay and concrete tiles as well as metal roofing installation onto concrete, metal or wooden structures. The tape can also be used on glass, polycarbonate, uPVC, epoxy coated surfaces and fibre cement boards.

### Technical Data

Needle penetration	50 - 65
Specific gravity	1.46 – 1.56

### Usage Instructions

1. Ensure that surfaces are clean, dry, dust free, oil free and sound.
2. Release sealant from release paper and press it sufficiently onto the surface for a complete contact.

### Caution

Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

### Disclaimer

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that result from the use of the information, due to the possibility of variations of processing or working conditions of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.