



Wood Skirting

Gap Between Wall & Cabinet

Perimeter Sealing



AS-1120 Ultra Flex Gaps Sealer

ALSEAL Ultra Flex Gap Sealer is a premium-grade, high-elastic acrylic sealant for both external and internal sealing applications. Formulated with enhanced UV resistance, it can withstand up to 25% movement. It's paintable and designed for sealing gaps and joints where significant movement or vibration is expected.

Applications:

It's ideal for both external and internal sealing tasks. It's particularly suitable for sealing building joints that are subject to movement, such as door and window joints, cabinet and wardrobe installation, and skirting on wood flooring. It adheres well to a range of substrates, including metal, PVC, wood, concrete, gypsum boards, reinforced cement boards, and marble.

Approvals / Specifications:

- ▶ ASTM C920, Type S, Grade NS, Class 25, Use NT, M
- ▶ Good Environmental Choice Australia (GECA) certified
- ▶ Low VOC - USEPA Method 24 and SCAQMD Method 304-91 under SCAQMD Rule 1168

Available colour: White

Product Code	Content	Carton Quantity
AS-1120	450 g / Cartridge	24 / Carton



Features:

- ✓ ±25% Movement capability
- ✓ Exterior & Interior sealant applications
- ✓ Paintable
- ✓ Permanently flexible & easy clean up