

ALSEAL AS-1720 is a water-based indoor/outdoor air duct sealant for sealing fabricated joints and other types of air ducts. It performs as a tough and flexible adhesive and sealant on the joints and seams, thereby effectively blocks the infiltration of gases, dust and other contaminants and the exfiltration of conditioned air. Excellent coverage rate can be achieved with easy brush-on application, which helps reduce installation cost. The thixotropic consistency of the sealant allows easy application by brush, trowel, hand, spray or extrusion. It is compliant with FDA 21 CFR 177.2600 (e) & (f).

Applications:

Ideal for sealing fabricated joints and seams of sheet metal air ducts, fibreglass duct board, thermal insulation, crawl space vapour barriers, house wrap, and other types of air ducts.

Approvals / Specifications:

- ► LEED v4 EQc2 compliant
 - Low VOC Content USEPA Method 24 and SCAQMD Method 304-91 under SCAQMD Rule 1168
 - Low VOC Emission CDPH Standard Method v1.2- 2017
- ► FDA 21 CFR 177.2600 (e) & (f).

Available colour: Grey

Product Code	Content	Carton Quantity
AS-1720-4K	4.0 kg / Pail	4 / Carton
AS-1720-20K	20.0 kg / Pail	1 / Carton

Features:

- ✓ Environmentally Friendly Sealant
- Low VOC and low odour
- ✓ Safe for Food Contact
- ✓ Paintable
- Excellent workability
- Crack and peel resistant
- ✓ Slump resistant
- ✓ High solid content
- Low shrinkage