

Wooden Floorboards

Skirting Boards

Wooden Staircase



## AS-4033 MS PRO

ALSEAL MS PRO is a single-component, elastomeric, and fast-curing sealant adhesive formulated using advanced MS Polymer technology. It's recommended for a wide range of indoor and outdoor sealing and bonding applications.

### Applications:

Recommended for bonding and sealing various materials in buildings, including wooden floorboards, skirting boards, architraves, plywood, fibre cement board, concrete, cured levelling compounds, moisture vapour barriers, OSB (underlayment grade), particle board, rubber underlay, gypsum board, ceramic tiles, stone, terrazzo, radiant-heated subfloors, metal decking, steel, and aluminium.

It can also be used to seal common building joints like wall panel joints and window frame perimeters, particularly when the sealant requires painting. Other recommended applications include sealing GRC panel systems, brick walls, anodised aluminium, masonry, porcelain, coated metals, finished wood, epoxy and polyester panels, uPVC, polystyrene, and stainless steel.

### Approvals / Specifications:

- ▶ Good Environmental Choice Australia (GECA) certified
- ▶ Low VOC - USEPA Method 24 under SCAQMD Rule 1168

**Available colour:** Redwood

### Features:

- ✓ Permanently flexible
- ✓ Excellent workability
- ✓ Excellent weathering resistance
- ✓ Paintable
- ✓ Low static charge – Less dirt streaking
- ✓ No silicone oil – Non-staining on adjacent substrates
- ✓ No isocyanate – No blistering
- ✓ No solvent – No shrinkage & non corrosive
- ✓ Bonds most substrates without primer

Product Code	Content	Carton Quantity
AS-4033S	600 ml / sausage	20 / Carton