



Wood Flooring



Furniture Repair



AS-5560 Timber Adhesive 5560

AL SEAL Timber Adhesive 5560 is a fast setting water-based adhesive suitable for bonding in wood working applications. It is white colour before drying but will turn into a clear and colourless dried film. It dries to form a strong bond between timbers, and is resistant to normal hygrometric movements of wood and the thermal expansion of substrates. It can be applied smoothly and can be cleaned up with water.

Applications:

Ideal for the bonding of moisture sensitive timber in wood flooring applications, including parquet or morsaic, industrial parquet and floorboards of all types of wood, multi-layer pre-finished parquet of small format. It may be used on cement-based screeds, wooden substrates, shipboard panels, Masonite panels etc.

Approvals / Specifications:

- ▶ Low VOC - USEPA Method 24 SCAQMD Method 303-91 under SCAQMD Rule 1168

Available colour: Clear

Features:

- ✓ Fast setting
- ✓ High solid content (Low water content)
- ✓ Bonding moisture sensitive timber
- ✓ Dry colour: Clear
- ✓ Notched trowel ridges will hold firm

Product Code	Content	Carton Quantity
AS-5560-500	500 g / Bottle	24 / Carton
AS-5560-5K	5 kg / Jerry Can	4 / Carton
AS-5560-20K	20 kg / Paper Carton	-
AS-5560-20K	20 kg / Jerry Can	-