

Technical Data Sheet

AS-9100B Water Tank Sealant



Physical Properties

Principal composition:
Synthetic rubber

Appearance:
Black

Characteristics:
Tough and resilient

Sealing property:
Excellent

Water resistance:
Excellent

Toxicity:
Non-toxic

Service temperature:
-30 °C to 80 °C

Storage:
Avoid from direct sunlight exposure and heat source. Keep under cold and shaded place.

Shelf life:
12 months

Packaging:

Product	Quantity/ carton
AS-9100B-45413M	4 rolls (45mm x 4mm x 13m)

Description

ALSEAL Water Tank Sealant is an extruded, ever-tacky, waterproof, high performance butyl sealant. It is non-toxic and safe for use in contact with drinking water.

Features

- ◆ Waterproof
- ◆ Safe for drinking water

Applications

Specially formulated for permanently sealing flange joints of sectional water tanks.

Technical Data

Needle penetration	30 - 45
Specific gravity	1.48 – 1.58

Usage Instructions

1. Ensure the target surfaces are clean, dry, dust-free and oil-free.
2. Peel off the release paper and press the sealant strip onto the surfaces to ensure good contact before fastening it with a bracket to achieve a permanent, water-tight seal.

Caution

Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

Disclaimer

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that result from the use of the information, due to the possibility of variations of processing or working conditions of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.