



ALSEAL
Stick to Alseal's Quality



Timber Flooring



Engineered Wood Flooring



AS-5590 Timber Adhesive 5590

ALSEAL Timber Adhesive 5590 is a fast setting water-based adhesive featuring medium solid content (medium water content) thus suitable for bonding of various types of moisture sensitive timber in wood flooring applications. It is white colour before drying but will change into a clear and colourless dried film. It dries to form a strong bond between timbers, and is resistant to normal hygrometric movements of wood and the thermal expansion of substrates. It can be applied smoothly and easily cleaned up with water.

Applications:

Ideal for the bonding of moisture sensitive timber in wood flooring applications, including parquet, industrial parquet and floorboards of all types of wood, multi-layer pre-finished parquet of small format. It may be used on cement-based screeds, wooden substrates, ship-board panels, Masonite panels etc.

Available colour: White (Dries clear)



Features:

- ✓ Fast setting
- ✓ Medium solid content (Medium water content)
- ✓ Bonds moisture sensitive timber
- ✓ Dried colour: Clear
- ✓ Notched trowel ridges will hold firm

| Product Code | Content | Carton Quantity |
|---------------|----------------|-----------------|
| AS-5590PP-20K | 20 kg / Pail | - |
| AS-5590-20K | 20 kg / Carton | - |
| AS-5590OV | 500 g / Bottle | 24 |