

Technical Data Sheet

AS-5400 Bituminous Underseal



Physical Properties

Principal composition:
Bitumen and resin

Appearance:
Black

Storage:
Best kept in a well-sealed container and stored in a cool and dry place, below 30 °C.

Shelf life:
12 months

Packaging:

Size	Quantity/ carton
3.0 kg	6 tins
18.0 kg	1 tin

Description

ALSEAL Bituminous Underseal is an underbody and sound deadener sealant with rust-preventing properties, suitable for use in the automobile & building industries. It is suitable for spray or brush application.

Applications

Suitable for use in the automobile and building industries.

Features

- ◆ Sound deadener
- ◆ Prevents rust
- ◆ Spray or brush application

Technical Data

Solvents	: Aliphatic solvent
Solid content	: 60 ± 2 %
Specific gravity	: 1.10 ± 0.05
Viscosity	: 13,000 – 14,000 cPs

Usage Instructions

1. Clean cracks, nail heads or holes and leave them to dry.
2. Fill cracks with sealing compound using towel or putty knife.

Caution

Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

Disclaimer

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.