

SECTION 1: Identification of the hazardous chemical and of the supplier

1.1. Product identifier

Name : AS-7000 Paint Remover

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coatings and paints, thinners, paint removers

1.4. Supplier's details

Manufacturer

Alseal Marketing Sdn. Bhd.
No.86, Jalan Industri 3/3,
Rawang Integrated Industrial Park,
48000 Rawang, Selangor, Malaysia.
T +603-60942088 - F +603-60992930
info@alsealmarketing.com

1.5. Emergency phone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to Industry Code of Practice on chemicals classification and hazard communication (2014)

Flam. Liq. 3	H226
Acute Tox. 4 (Oral)	H302
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Carc. 2	H351
STOT SE 2	H371
STOT SE 3	H336

2.2. Label elements

Labelling according to Industry Code of Practice on chemicals classification and hazard communication (2014)

Hazard pictograms (GHS MY) :



Signal word (GHS MY) :

Warning

Contains :

DICHLOROMETHANE; methanol

Hazard statements (GHS MY) :

H226 - Flammable liquid and vapour.
H302 - Harmful if swallowed.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H351 - Suspected of causing cancer.
H371 - May cause damage to organs.

Precautionary statements (GHS MY) :

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.

2.3. Other hazards not contributing to the classification

No additional information available

SECTION 3: Composition and information of the ingredients of the hazardous chemical

3.1. Substances

Not applicable

3.2. Mixtures

AS-7000 Paint Remover

Safety Data Sheet

According to ICOP 2014

Name	Product identifier	%	Classification according to Industry Code of Practice on chemicals classification and hazard communication (2014)
DICHLOROMETHANE	(CAS-No.) 75-09-2	70 – 90	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336
methanol	(CAS-No.) 67-56-1	1 – 10	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
EAC code	: •3YE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
-------------------------	---

AS-7000 Paint Remover

Safety Data Sheet

According to ICOP 2014

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

methanol (67-56-1)	
Malaysia - Occupational Exposure Limits	
Local name	Metanol (Metil alkohol) # Methanol (Methyl alcohol)
PEL TWA (mg/m ³)	262 mg/m ³
PEL TWA (ppm)	200 ppm
Remark (MY)	(kulit # skin)
USA - ACGIH - Occupational Exposure Limits	
Local name	Methanol
ACGIH TWA (ppm)	200 ppm
ACGIH STEL (ppm)	250 ppm
Remark (ACGIH)	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2020
USA - ACGIH - Biological Exposure Indices	
Local name	METHANOL
Biological Exposure Indices (BEI)	15 mg/l Parameter: Methanol - Medium: urine - Sampling time: End of shift - Notations: B, Ns
Regulatory reference	ACGIH 2020

Exposure limit values for the other components

No additional information available

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):

AS-7000 Paint Remover

Safety Data Sheet

According to ICOP 2014



Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: Colourless
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Melting point, Freezing point	: Melting point: Not applicable Freezing point: No data available
Boiling point	: No data available
Flash point	: ≈ 38 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Explosive limits	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: Relative density: ≈ 1.20
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Auto-ignition temperature	: No data available.
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

SECTION 10: Stability and reactivity

Reactivity	: Flammable liquid and vapour.
Chemical stability	: Stable under normal conditions
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use
Conditions to avoid	: Avoid contact with hot surfaces, Heat, No flames, no sparks. Eliminate all sources of ignition
Incompatible materials	: No data available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
ATE MY (oral)	1182.033 mg/kg bodyweight
Skin corrosion/irritation	: Causes skin irritation. pH: No data available
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause damage to organs. May cause drowsiness or dizziness.

AS-7000 Paint Remover

Safety Data Sheet

According to ICOP 2014

DICHLOROMETHANE (75-09-2)	
STOT-single exposure	May cause drowsiness or dizziness.
methanol (67-56-1)	
STOT-single exposure	Causes damage to organs.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

12.2. Persistence and degradability

AS-7000 Paint Remover	
Persistence and degradability	No additional information available

12.3. Bioaccumulative potential

AS-7000 Paint Remover	
Bioaccumulative potential	No additional information available

12.4. Mobility in soil

AS-7000 Paint Remover	
Mobility in soil	No additional information available

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available

SECTION 13: Disposal information

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapours may accumulate in the container.

SECTION 14: Transportation information

14.1. UN number

UN-No.(UN RTDG)	: 1263
UN-No. (IMDG)	: 1263
UN-No. (IATA)	: 1263

14.2. Proper Shipping Name

Proper Shipping Name (UN RTDG)	: PAINT RELATED MATERIAL
Proper Shipping Name (IMDG)	: PAINT RELATED MATERIAL
Proper Shipping Name (IATA)	: Paint

14.3. Transport hazard class(es)

UN RTDG

Transport hazard class(es) (UN RTDG)	: 3
Danger labels (UN RTDG)	: 3



AS-7000 Paint Remover

Safety Data Sheet

According to ICOP 2014

IMDG

Transport hazard class(es) (IMDG) : 3

Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3

Danger labels (IATA) : 3



14.4. Packing group

Packing group (UN RTDG) : II

Packing group (IMDG) : III

Packing group (IATA) : III

14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

- UN RTDG

Special provisions (UN RTDG) : 163, 367

Limited quantities (UN RTDG) : 5L

Excepted quantities (UN RTDG) : E2

Packing instruction (UN RTDG) : P001, IBC02

Special packing provisions (UN RTDG) : PP1

Portable tank and bulk container special instructions (UN RTDG) : T4

Portable tank and bulk container special provisions (UN RTDG) : TP1, TP8, TP28

- IMDG

Special provisions (IMDG) : 163, 223, 367, 955

Limited quantities (IMDG) : 5 L

Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : P001, LP01

Special packing provisions (IMDG) : PP1

IBC packing instructions (IMDG) : IBC03

Tank instructions (IMDG) : T2

Tank special provisions (IMDG) : TP1, TP29

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS

EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER

Stowage category (IMDG) : A

Properties and observations (IMDG) : Miscibility with water depends upon the composition.

- IATA

PCA Excepted quantities (IATA) : E1

AS-7000 Paint Remover

Safety Data Sheet

According to ICOP 2014

PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

14.8. Hazchem or Emergency Action Code

EAC code : •3YE.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Version : 1.0
Issue date : 26/11/2020

Full text of H-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 1	Specific target organ toxicity — Single exposure, Category 1
STOT SE 2	Specific target organ toxicity — Single exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H370	Causes damage to organs.
H371	May cause damage to organs.

Safety Data Sheet (SDS), Malaysia

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.