

Aluminium Composite Panel



Fire Compartment Joints



Underground Tunnel Joints



AS-202 Fire Retardant Silicone Sealant

ALSEAL Fire Retardant Silicone Sealant is a single-component, gun-grade, ready-to-use neutral silicone sealant formulated to form an elastomeric fire retardant seal in construction applications. It helps control the spread of fire, smoke and toxic fumes within a given area surrounded by firewalls for a period of up to four hours, depending on joint configuration.

Applications:

Recommended for firestop sealing of interior and exterior building and construction joints, where a fire rating of up to 4 hours is required. It may be used to seal vertical and horizontal joints between metals, masonry, concrete and other common construction materials.

Approvals / Specifications:

- ▶ BS EN 1366-4:2006 Fire Resistance Tests
- ▶ AS 1530.4:2014 Methods for Fire Tests on Building Materials
- ▶ ASTM C920 & ASTM C719, Type S, Grade NS, Class 50, Use NT, A
- ▶ Low VOC - USEPA Method 24 under SCAQMD Rule 1168 & USEPA Method 310

Available colours: Matte grey & matte black

Product Code	Content	Carton Quantity
AS-202	300 ml / Cartridge	24 / Carton



Features:

- ✓ Fire rating up to 4 hours
- ✓ ±50% movement capability
- ✓ Excellent weather and UV resistance
- ✓ Excellent adhesion to most substrates
- ✓ Matte finish