

Technical Data Sheet

AS-1226 Shoe Adhesive

Physical Properties

Appearance:

Viscous liquid

Odour:

Sweet Smelling

Application temperature:

-10 °C to 40 °C

Service temperature:

-10 °C to 60 °C

Storage:

Store in a dry and cool place with temperature below 30 °C.

Shelf life:

24 months

Packaging:

Content	Quantity/ carton
20 mL tube carded	144



Description

ALSEAL Shoe Adhesive is a solvent-based (toluene-free) adhesive specially formulated for do-it-yourself shoe and leather goods repair jobs. It is easy to use, fast setting, and economical. It also offers superior bonding strength with excellent water and heat resistant.

Applications

Ideal for bonding of natural or artificial leather goods.

Features

- ◆ Toluene-free
- ◆ Excellent adhesion
- ◆ Flexible bonding
- ◆ Water and heat resistant
- ◆ Dries transparent

Technical Data

Solids	: 15 – 17 %
Viscosity at 25°C (Brookfield LV 4, 50 rpm)	: 2,000 – 3,000 cPs
Specific gravity	: 0.86 ± 0.02

Usage Instructions

1. Surfaces must be clean, dry and free of dirt, grease, oil or water. Puncture tube with cap.
2. Apply adhesive onto both sides of the surface to be bonded and allow solvent to evaporate (2 – 10 minutes).
3. Once the adhesive is tacky, press both surfaces firmly. Maintain pressure for at least 24 hours.
4. Replace cap after use and store in a cool, dry place.

Caution

Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe fumes. Use only outdoors or in a well-ventilated area. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Store in a well-ventilated place. Keep cool. Store locked up.

Disclaimer

Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.