

SAVANA DIESEL TURBO



SAE Grade 15W/40

Performance Level API: CG-4/SF

ACEA E2-96, B4-98, B3-98, A3-98, MB 229.1, 228.0/1, MAN 270/271, VOLVO VDS, MACK EO-L, MTU/DDC TYPE-1, ALLISON-C4

Product Description SAVANA Diesel Turbo is high performance diesel engine oil blended from superior quality base stock and high performance additives. Its superior stable viscosity index improver does not shear off at operating conditions of high load and elevated temperatures. It has detergent/dispersant, anti-wear, anti-oxidation, and pour point depressant additives that ensure the oil to perform under the most severe operating conditions.

Main Benefits

- High level of detergent/dispersant keeps engine clean.
- Excellent chemical stability protects against formation of lacquer and hard carbon deposits.
- Superior wear control protects engine against cylinder bore polishing, and wear on cam, tappets and bearings.
- Longer drain with quality reserve.

Application Diesel Turbo is recommended for use in heavily loaded turbo charged diesel or gasoline engines in off-highway and on-highway service.

Physical Characteristics	Test Method	Typical Values
SAE Grade		15W/40
Specific Gravity @ 60/60 F	ASTM D-4052	0.888
Viscosity Kinematic @ 40 °C, cSt @ 100 °C, cSt	ASTM D-445	110.00 14.50
Viscosity Index	ASTM D-2270	135
Flash Point, COC, °C	ASTM D-92	224
Pour Point, °C	ASTN D-97	-27