

SAVANA SYN MULTI GEAR AUTO TRANSMISSION OIL



SAE Viscosity Grade ATF

Product Description SAVANA SYN-MV formulation was developed to meet the demands of major Asian OEMs, and yet, fully capable of satisfying the requirements set by US/European OEMs. SYN-MV is blended with synthetic base stocks and the latest advanced additive technology to achieve a fully balance frictional characteristics for smooth shifting, better power transfer/acceleration and excellent anti-shudder properties. This truly multi-vehicle fluid shows significant improvements corrosion and wears performances over genuine oils.

The synergistic effect of the premium components in **SAVANA SYN-MV** ensures excellent shear stability and oxidation resistance for longer service life. It provides exceptional sludge and varnish control, and offers superior gear and bearing durability. It also exhibits superb low temperature performance.

SAVANA SYN-MV exceeds the requirements of JASO-1A performance standards demanded by the Japanese Automobile Manufactures. This Standard is recognized by Japanese OEMs in approving ATF for use in their vehicles. SYN-MV has one of the most performance claims in the industry:

Features

- Optimum friction durability for outstanding vehicle performance
- Excellent thermal stability and oxidation resistance for prolonged fluid life
- Anti-wear protection for transmission and hydraulic system
- Detergents and dispersants to improve system cleanliness
- Compatible with most seal materials and other synthetic or mineral fluids
- Better fuel economy
- Improves driver comfort through smooth shifting
- Constant high level of torque capacity for better power transfer and acceleration
- Reduces emissions

Applications

- Recommended for service fill in all passenger car and light duty truck or commercial vehicles that require an automatic transmission fluid meeting any of the above standards.
- It may also be used in industrial and mobile hydraulic systems operating over a wide range of temperature.

Physical Characteristics	Typical Value
Grade	ATF
Density, kg/ liter @ 15 °C	0.856
Appearance	Red
Kinematic Viscosity, mm ² / s @ 40 °C	37.00
Kinematic Viscosity, mm ² /s @ 100 °C	7.40
Viscosity Index	171
Brookfield Viscosity @ -40 °C , cP	13020
Flash Point , COC , °C	200
Pour Point, °C	-48

PERFORMANCE STANDARDS

Claim/ Performance	Claim
Acura ATF-Z1	SFU
Aisin Warner JWS 3309 (T-IV) & JWS 3324 (WS), AW-1	SFU
Allison C-3 & C-4	SFU
American Motors ATF +3 (MS7176-E), ATF +4 (MS9602)	SFU
ATF RED 1, RED 1K	SFU
Audi 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A)	SFU
Audi/VW G 052 025-A2	SFU
Audi G 052 162-A1/A2	SFU
Audi G 055 025 A2 (JWS 3309)	SFU
Audi G 052 162 (ZF Lifeguard fluid 5) (ZF No. S671 090 170)	SFU
Audi/VW G 060 162 (ZF Lifeguard fluid 8) (ZF No. S671 090 312)	SFU
Audi/VW G 152 990	SFU
Audi/VW G 055 540 (A2)	SFU
Audi/VW G 052 055	SFU
Bentley PY112995PA	SFU
BMW JWS 3309 (T-IV)	SFU
BMW LA2634	SFU
BMW LT71141 (ZF 5 HP 18FL/19FL/24A)	SFU
BMW ZF 5HP18FL, 5HP24, 5HP30	SFU
BMW 7045E (83 22 0 026 922)	SFU
BMW ETL-8072B (83 22 9 407 807)	SFU
BMW MINI	SFU
Bosch TE-ML 09	SFU
CAT TO-2	SFU
Chrysler ATF+, +2, +3 (MS 7176E), +4 (MS 9602)	SFU
Chrysler / Dodge MOPAR AS 68 RC (T-IV), JWS 3309	SFU
Chrysler / Dodge /Jeep 05127382AA	SFU
Chrysler / Dodge /Jeep 68043742AA	SFU
Chrysler / Dodge /Jeep 68171866AA	SFU
Daewoo LT71141	SFU
Daihatsu AMMIX ATF D-II	SFU
Daihatsu AMMIX ATF D-III SP	SFU
Esso LT 71141	SFU
FIAT T-IV type, JWS 3309	SFU
Ford MERCON®	SFU
Ford WSS-M2C-938A/SF, XT-10 QLV	SFU
Ford FNR5	SFU
Ford WSS M2C 138CJ, M2C 166H	SFU
Ford M2C166H	SFU
Ford WSS M2C 138CJ, 166H	SFU
Ford WSS M2C 922AI, 924A (XT-8-QAW) JWS 3309	SFU
Ford XT-2-QDX (M)	SFU
Ford XT-2-QDM (Syn)	SFU
Ford ESPM2C166H, XL-12	SFU
Fuso ATF-II	SFU
Fuso ATF-SPIII	SFU
Fuso ATF- A4	SFU
GM9986195 (Aisin AW, JWS 3309)	SFU
GM TASA	SFU
GM DEXRON® -II, IID, IIE	SFU
GM DEXRON® -IIIG, IIIH	SFU
GM 1940700, 1940767	SFU
GM 21005966, 22717466	SFU
GM 88900925, 9986195, 93160393	SFU
GM/GMC/Opel/Saturn AW1, VI	SFU
GM/GMC/Opel/Saturn 88863400 88863401	SFU

Claim/ Performance	Claim
Hino Blue Ribbon ATF	SFU
Honda ATF-ZI (except in CVTs)	SFU
Honda ATF Ultra II	SFU
Honda DW-I	SFU
Honda Type 3.1	SFU
Hyundai/Kia SP-IV, SPH-IV	SFU
Hyundai/Kia SP-IV M (SP4-M)	SFU
Hyundai/Kia SP-IV-RR	SFU
Hyundai/Kia Dex-II/SP-II, SP-III	SFU
Hyundai/Kia JWS 3314	SFU
Hyundai/Kia JWS 9683	SFU
Hyundai/Kia 040000C90SG	SFU
Hyundai/Kia NUMM0400 CH020 RED-1	SFU
Idemitsu K17 3100 PL085	SFU
ISUZU BESCO ATF-II, ATF-III	SFU
ISUZU BESCO ATF SP	SFU
ISUZU SCS Fluid	SFU
Jaguar ATF 3403 M115, ATF 403-M115,	SFU
Jaguar ATF LT71141, ZF 5HP24	SFU
Jaguar JLM20238	SFU
Jaguar ATF 3403 JLM20238,	SFU
Jaguar K17	SFU
Jaguar JLM 20292	SFU
Jaguar Fluid 8432	SFU
JASO M315-2013 1A	SFU
JASO M315-2013 1A-LV	SFU
JASO M315-2013 2A	SFU
JEEP ATF+3, +4	SFU
KIA ATF SP-II, SP-III, SP-IV, SP-IVM, Red 1	SFU
Land Rover LR023288	SFU
Lexus JWS 3309	SFU
MAN 339A	SFU
Mazda ATF D-II	SFU
Mazda ATF M-III	SFU
Mazda ATF M-V	SFU
Mazda ATF FZ	SFU
Mazda ATF F-1	SFU
Mazda ATF S-1	SFU
Mazda ATF N-1	SFU
Mazda ATF 3317	SFU
MB 236.1	SFU
MB 236.2	SFU
MB 236.3	SFU
MB 236.5	SFU
MB 236.6	SFU
MB 236.7	SFU
MB 236.8	SFU
MB 236.9	SFU
MINI COOPER T-IV	SFU
Mitsubishi Diaqueen SK	SFU
Mitsubishi Diaqueen SP-II, SP-III, SP -IV	SFU
Mitsubishi Diaqueen AW	SFU
Mitsubishi Diaqueen J2	SFU
Mitsubishi Diaqueen J3	SFU
Mitsubishi Diaqueen ATF PA	SFU
NAG 1 (Chrysler, Jeep, Cherokee)	SFU
Nissan Matic Fluid C	SFU
Nissan Matic Fluid D	SFU

Claim/ Performance	Claim
Nissan Matic Fluid J	SFU
Nissan Matic Fluid K	SFU
Nissan Matic Fluid S	SFU
Opel / GM 19 40 700	SFU
Opel / GM 19 40 767	SFU
Opel / GM 21005966 Transaxle	SFU
Opel / GM 22 17466	SFU
Opel / GM 88900925	SFU
Opel / GM 9986195	SFU
Peugot ZF 4HP20	SFU
Peugot / Citeron Z 000169756	SFU
Porsche ZF 5HP19FL, ZF 5HP20, LT71141	SFU
Porsche ATF 3403-MI15,	SFU
Porsche T-IV (JWS 3309)	SFU
Porsche 000 043 205 09	SFU
Porsche 000 043 205 28	SFU
Porsche 999 917 547 00 (A2)	SFU
Porsche Z 000169759	SFU
Renault DPO / AL4	SFU
Renault Matic D2	SFU
Renault Samsung SATF-D	SFU
Saab T-IV (JWS 3309)	SFU
Saab 93 165 147	SFU
Saturn T-IV (JWS 3309)	SFU
Scion (all vehicle)	SFU
Shell 3403, M115, LA 2634, L 12018	SFU
Shell M-1375.4	SFU
Shell L12108	SFU
Ssang Yong DSIH 5M-66	SFU
Subaru ATF	SFU
Subaru K0140Y0700	SFU
Subaru ATF 5AT	SFU
Subaru Dexron®-II	SFU
Subaru ATF, ATF HP	SFU
Suzuki ATF AW-1	SFU
Suzuki AT OIL 5D06	SFU
Suzuki ATF 2326	SFU
Suzuki ATF 2384K	SFU
Suzuki JWS 3309	SFU
Suzuki ATF 3314	SFU
Suzuki ATF 3317	SFU
Texaco 7045-E	SFU
Texaco 8072B	SFU
Texaco N402	SFU
Toyota ATF D-II	SFU
Toyota ATF D-III	SFU
Toyota ATF T-III	SFU
Toyota ATF T-IV	SFU
Toyota ATF WS	SFU
Vickers M2950-S, I-286-S	SFU
Voith 55.6335.xx (G607)	SFU
Volvo 97325, 97335	SFU

Claim/ Performance	Claim
Volvo CE 97340	SFU
Volvo PN 1161540 / 1161640	SFU
VW 5 HP (ZF 5 HP 30)	SFU
VW 5HP (18FL, 30)	SFU
VW 5HP (19FL, 24A)	SFU
VW G-055-025 A2 (JWS 3309)	SFU
VW G-055-540 (A2)	SFU
VW G 055 162 (ZF Lifeguard fluid 5)	SFU
VW G 055 162-A2, A6 (ZF Lifeguard fluid 6 Plus)	SFU
VW G 060 162 (ZF Lifeguard fluid 8)	SFU
VW G US 000 162	SFU
VW TL 521 62	SFU
ZF all 3 & 4 speed transmission	SFU
ZF 8 speed transmission	SFU
ZF 9 speed transmission	SFU
ZF TE-ML 05L	SFU
ZF TE-ML 09	SFU
ZF TE-ML 11A, 11B	SFU
ZF TE-ML 21L	SFU

(1) "SFU" = This product is suitable for use against the given claim or performance
(2) Not to be used for DCT or CVT applications